



Product Description: 12W Square Low Profile Mini LED Downlight 150mm Diameter

Fixed 12W square low profile mini LED downlight. Highly efficient with up to 92lm/W and a high Power Factor of 0.9. Supplied with remote constant current driver. Non-Dimmable.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
AU-DL10312SS/30	12	3000	1040	87	120	Satin Silver	Non Dimmable
AU-DL10312SS/40	12	4000	1100	92	120	Satin Silver	Non Dimmable
AU-DL10312W/30	12	3000	1040	87	120	White	Non Dimmable
AU-DL10312W/40	12	4000	1100	92	120	White	Non Dimmable

Line Drawing

Polar Curve

Colour

Feature & Benefits

- LED downlight supplied with remote LED driver
- Non-dimmable driver included
- Colour rendering index (Ra) 80
- (L70) at a 50,000 hour lifetime
- Suitable for office or commercial applications

Product Specs:

Input Voltage	100~240V DC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP20
Lifetime L70 (hrs)	50000hrs	Width (mm)	150
Length (mm)	150	Weight (Kg)	0.342
Cutout Length (mm)	135	Cutout Width (mm)	135
Height (mm)	43	Product Type	Downlights
Cutout Diameter (mm)	135-	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	40°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.