Product Description: Modi™ 19W Non-Dimmable Downlight

Fixed, dimmable 19W IP20 LED downlight. Die-cast aluminium with frosted polycarbonate diffuser, designed to replace traditional PL downlights. Driver options include Mains, Dali and 1-10V dimmable drivers (sold separately). Suitable for cut-out of 150mm. Emergency and Baffled versions available. Interchangeable bezels available in round, square and drop glass options.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-DL17519AK/40	19	4000	1650	87	90	Black
AU-DL17519AK/40D	19	4000	1650	87	90	Black
AU-DL17519AK/40V	19	4000	1650	87	90	Black

Line Drawing



Polar Curve

Colour

Feature & Benefits

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP20
Lifetime L70 (hrs)	35000hrs	Overall Diameter (mm)	170
Height (mm)	67	Product Type	Downlights
Cutout Diameter (mm)	150-	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	25°C		

Compliance & Approvals:

Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.