

Product Description: MR16 IP65 Fire Rated Downlight

Superb basic MR16 Fire rated IP65 downlight. This fitting is rated to withstand up to 90 minutes in a real fire without breaking the safety barrier. Can be used in Bathroom ceilings. It looks great once installed and has a cutout diameter of 72 mm.

SKU Code	Beam Angle	Finish Colour
AU-DLL993MW	36	
AU-DLL993PB	36	
AU-DLL993PC	36	
AU-DLL993SN	36	
AU-DLL993SS	36	Satin Silver
AU-DLL993W	36	

Line Drawing

Polar Curve

Colour

## Feature & Benefits

- Registered Community Design 390612-0001/2/3
- UK Patent GB2426321
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- 50W MR16 halogen lamp included

## Product Specs:

Input Voltage	12~12V AC	IP Rating	IP65
Lifetime L70 (hrs)	3000hrs	Lamp Base	GU5.3
Overall Diameter (mm)	86	Weight (Kg)	0.302
Height (mm)	155	Cutout Diameter (mm)	72-

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.