

Product Description: GU10 IP65 Fire Rated Downlight

SKU Code	Wattage
AU-DLM623PC	70
AU-DLM623SN	70
AU-DLM623SS	70
AU-DLM623W	70

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Registered Community Design 000349725-0002/3 (fitting)
- Patent pending
- Integrated heat sink allows downlights to be covered with thermal insulation. Downlight insulation guard not required
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- For use with Aluminium Reflector lamps ONLY
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- 2 Year guarantee (excludes lamp)

Product Specs:

Input Voltage	220~240V AC	Lifetime L70 (hrs)	5000hrs
Lamp Base	GU10	Overall Diameter (mm)	98
Weight (Kg)	0.413	Height (mm)	116
Cutout Diameter (mm)	85-		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.