



Product Description:

Aurora GU10 IP65 Fire Rated Downlight

IP65 GU10 Fire Rated Downlight with an integrated intumescent material that completely seals the downlight and cut-out in the event of a fire. Suitable for use with LED Bulbs. Downlight has been tested in 30, 60 and 90 minute fire rated ceilings. Acoustic rated, suitable for an internal or separating floor to provide sound insulation. Cast Aluminium and Pressed Steel body.

Finish Colour
Matt White
Polished Brass
Polished Chrome
Satin Nickel
Satin Silver
White

Line Drawing Polar Curve Colour

## Feature & Benefits

- Registered Community Design 390612-0001/2/3
- UK Patent GB2426321
- Integrated intumescent material
  Tested to BS476 Part 21 completely seals the downlight and cut-out in the event of a
- Tested in 30, 60 & 90 minute fire rated ceilings
- BS EN ISO 10140-2: 2010 & BS EN ISO 10140-3: 2010 + A1: 2015 (acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation

## **Product Specs:**

Input Voltage	220~240V AC
IP Rating	IP65
Overall Diameter (mm)	86
Height (mm)	155
Cutout Diameter (mm)	72-

Ir	nput Frequency	50/60HZ
L	amp Base	GU10
V	Veight (Kg)	0.349
P	Product Type	Downlights,Fire-Rated Downlight

## Compliance & Approvals:













This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.