Product Description: GX53 13W Adjustable Rated Downlight

SKU Code	Colour
AU-DLT222PB	2700
AU-DLT222PC	2700
AU-DLT222SN	2700
AU-DLT222W	2700

Line Drawing

Polar Curve

Colour

Feature & Benefits

- UK Patent GB2426321
- 13W GX53 Compact fluorescent low energy fire rated downlight
- Allows compliance with the Building Regulations Approved document L1A/B requiring the use of energy efficient luminaires in dwellings when used with a suitable lamp
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- 2 Year guarantee

Product Specs:

Input Voltage	220~240V AC	Lamp Base	GX53
Overall Diameter (mm)	140	Weight (Kg)	0.6
Height (mm)	115	Cutout Diameter (mm)	125-

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.