




Product Description: Eclips 35W Adjustable Downlight


Part of the Eclips range, the 35W Adjustable COB Downlights are ideal to set accents within an installation such as the illumination of wall paintings along corridors or in meeting rooms. With a lumen package of 1892lm, the adjustable head creates an ideal wall wash effect. Spaces are further enhanced by applying Eclips accessories such as Mirror, Black or Matt Silver baffles, Honeycomb attachments or colour filters. Supplied with CRI80 as standard and SDCM<3, clients can also opt for CRI90 options to further enhance colour quality of the installation. Beam angles include 15°, 24° and 36°. L70 is 50,000 hrs.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour |
|--------------------|---------|--------|--------|-------------|------------|---------------|
| AU-EC35A1DTAK/30 | 35 | 3000 | 1892 | 55 | 15 | White |
| AU-EC35A1DTAK/40 | 35 | 4000 | 1892 | 55 | 15 | White |
| AU-EC35A1EMNDAK/30 | 35 | 3000 | 1892 | 55 | 15 | White |
| AU-EC35A1EMNDAK/40 | 35 | 4000 | 1892 | 55 | 15 | White |
| AU-EC35A1NDAK/30 | 35 | 3000 | 1892 | 55 | 15 | White |
| AU-EC35A1NDAK/40 | 35 | 4000 | 1892 | 55 | 15 | White |
| AU-EC35A2DTAK/30 | 35 | 3000 | 1892 | 55 | 24 | White |
| AU-EC35A2DTAK/40 | 35 | 4000 | 1892 | 55 | 24 | White |
| AU-EC35A2EMNDAK/30 | 35 | 3000 | 1892 | 55 | 24 | White |
| AU-EC35A2EMNDAK/40 | 35 | 4000 | 1892 | 55 | 24 | White |
| AU-EC35A2NDAK/30 | 35 | 3000 | 1892 | 55 | 24 | White |
| AU-EC35A2NDAK/40 | 35 | 4000 | 1892 | 55 | 24 | White |
| AU-EC35A3DTAK/30 | 35 | 3000 | 1892 | 55 | 36 | White |
| AU-EC35A3DTAK/40 | 35 | 4000 | 1892 | 55 | 36 | White |
| AU-EC35A3EMNDAK/30 | 35 | 3000 | 1892 | 55 | 36 | White |
| AU-EC35A3EMNDAK/40 | 35 | 4000 | 1892 | 55 | 36 | White |
| AU-EC35A3NDAK/30 | 35 | 3000 | 1892 | 55 | 36 | White |
| AU-EC35A3NDAK/40 | 35 | 4000 | 1892 | 55 | 36 | White |


Line Drawing




Polar Curve




15° Straight



15° Full Tilt



24° Straight



24° Full Tilt

Colour

Feature & Benefits

- Non Dimmable
- CRI 80 (Selected CRI 90 options available)
- Up to 89lm/W
- Beam angles available in 36°, 60° with 15° & 24° to special order
- Baffle/Filter/Reflector accessories available
- SDCM < 3
- 5 Year Warranty

Product Specs:

| | |
|--------------------------|-------------|
| Input Voltage | 220~240V AC |
| Power Factor | 0.95 |
| Lifetime L70 (hrs) | 50000hrs |
| Product Type | Downlights |
| Operating Temp. (Min) °C | -20°C |

| | |
|--------------------------|---------|
| Input Frequency | 50/60HZ |
| IP Rating | IP20 |
| Overall Diameter (mm) | 164 |
| Cutout Diameter (mm) | 150-150 |
| Operating Temp. (Max) °C | 50°C |

Compliance & Approvals:

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.