



Product Description: 80mm Diameter Firehood

Fully breathable fire hood for low/mains downlights allows heat from the lamp to be effectively dissipated preventing the terminal block and fitting from overheating. An intumescent material envelope expands to fill the hood and seal the downlight cut-out in the ceiling in the event of a fire in the room below.

| SKU Code | Finish Colour |
|------------|---------------|
| AU-FH150 | White |
| AU-FH150BK | Black |

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Unique self supporting and adjustable fixing method allows for installation in ceilings up to 35mm thick
- Tested to BS476 Part 21
- UK Patent GB2424693
- International PCT / GB03/003229
- Suitable for 30 and 60 minute fire rated ceilings

Product Specs:

| | |
|--------------|-------------|
| Width (mm) | 150 |
| Weight (Kg) | 0.211 |
| Product Type | Accessories |

| | |
|-------------|-----|
| Length (mm) | 150 |
| Height (mm) | 150 |

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.