

Product Description: 100W IP65 Floodlight

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle
AU-FLD101BLK	10	6400	560		110
AU-FLD101SS	10	6400	560	56	110

Line Drawing

Polar Curve

Colour

Feature & Benefits

- IP65 Mains voltage aluminium LED floodlight
- Ideal for lighting buildings, car parks, plazas, signs, trees, etc.
- Fitted with symmetric reflector
- Equipped with safety glass cover lens with silicon seal
- Powder coated corrosion resistant aluminium
- All external screws are stainless steel
- Very efficient >70Lm/W
- Non-dimmable

Product Specs:

Input Voltage	220~250V AC
Lifetime L70 (hrs)	50000hrs
Length (mm)	113
Height (mm)	87

IP Rating	IP65
Width (mm)	87
Weight (Kg)	0.537

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.