

Product Description:

83W IP65 Adjustable 58° Floodlight

| SKU Code | Wattage | Colour | Lumens | Beam Angle | |
|--|---|---|--------|-----------------------------|--|
| AU-FLD88358 | 83 | 4200 | 6450 | 58 | |
| | | | | | |
| Line Drawing | Polar Curve | | Colour | | |
| | | | | | |
| Feature & Benefits | | | | | |
| IP65 High power aluminium LED floodlights | Highly efficient heat dissipation design | Powder coated corrosion resistant finish | | n-dimmable ear guarantee | |
| Ideal for lighting buildings, parking lots, plazas, signs, trees, etc. | Mounting bracket may be adjusted 90° in both directions | All external screws are stainless steel | ζI | | |
| Equipped with safety glass cover lens with silicon seal | | | | | |

Product Specs:

| Input Voltage | 220~240V AC | IP Rating | IP65 |
|--------------------|-------------|-------------|------|
| Lifetime L70 (hrs) | 50000hrs | Width (mm) | 300 |
| Length (mm) | 405 | Height (mm) | 405 |

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.