

Product Description: T8 Fluorescent Suspended Light

SKU Code	Wattage	Colour	Lumens	Beam Angle
AU-FLT108BLK	8	4000	900	60
AU-FLT108W	8	4000	900	60

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Mains Voltage LED floodlight with PIR
- Three passive infrared sensors with varying degrees of protection, zones 1 & 3 covering 60°, zone 2 covering 100° with a total detection zone of 220° at 10m
- When movement is detected the motorised floodlight moves to that zone to illuminate the target
- Floodlight remains illuminated for 3 minutes after last movement is detected
- Dusk to dawn override switch to allow operation in daylight
- Non-dimmable

Product Specs:

Input Voltage	220~250V AC	Lifetime L70 (hrs)	30000hrs
Width (mm)	150	Length (mm)	165
Weight (Kg)	1.383	Projection (mm)	160
Height (mm)	150		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.