

Product Description: 10W IP65 Fixed Fire Rated Downlight

SKU Code	Wattage	Colour	Lumens	Beam Angle	Finish Colour
AU-FRL901PC/30	9	3000	400	33	Polished Chrome
AU-FRL901PC/40	9	4000	410	33	Polished Chrome
AU-FRL901SN/30	9	3000	400	33	Satin Nickel
AU-FRL901SN/40	9	4000	410	33	Satin Nickel
AU-FRL901W/30	9	3000	400	33	White
AU-FRL901W/40	9	4000	410	33	White

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Registered Community Designs - 001861261/001926940
- UK Patent Application - 1212923.5
- IP65 high power LED fire rated downlight
- Integrated LED driver connected to loop-in / loop-out FASTFIX connector (Included)
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- Dimmable (AU-FRLD613, AU-FRLD312) and non-dimmable (AU-FRL603, AU-FRL302) versions available (dimmable with leading/trailing edge dimmers)
- 7 Year Warranty - *see www.aurora.eu.com for details

Product Specs:

Input Voltage	100~240V AC	IP Rating	IP65
Lifetime L70 (hrs)	75000hrs	Overall Diameter (mm)	88
Weight (Kg)	0.465	Cutout Diameter (mm)	65-72

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.