

Product Description:

m10™ 10W IP65 Baffle Dimmable Fire Rated Downlight - No IC Covers left

Baffled, fixed, integrated, fire rated 10W LED downlight with driver-on-board and high voltage, single source LED chip. Available in 4000K. Bezels available in White, Matt White, Polished Chrome and Satin Nickel. 40° fitted as standard. Rated to 30, 60 and 90 minute fire ceilings. Unfortunately the Insulation coverable cap is no longer available and we have reduced the price of the unit accordingly to reflect this.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-FRLD813/27	10	2700	350	35	40	White
AU-FRLD813/30	10	3000	360	36	40	White
AU-FRLD813/40	10	4000	420	42	40	White
AU-FRLD813MW/40	10	4000	420	42	40	Matt White
AU-FRLD813PC/40	10	4000	420	42	40	Polished Chrome
AU-FRLD813SN/40	10	4000	420	42	40	Satin Nickel
AU-FRLD813W/40	10	4000	420	42	40	White

Line Drawing

Polar Curve

Colour

## Feature & Benefits

- Rated to 30, 60 & 90 minute fire ceilings
- icDOB™ (Driver on Board) for maximum reliability and lifetime - NO SEPARATE DRIVER REQUIRED
- CrystalCool™ next generation thermal management offers brighter light for longer
- Mains voltage single source HVLED™ chip eliminates overshadowing and offers controlled dimming
- Patented LEDchroic™ lens provides halogen appearance with LED efficiency, anti-glare and precise beam control
- ErP compliant - High colour rendering index (Ra) >80
- FastFix™ rapid install system - connector included
- BS EN 1365-2:2000 (Fire resistance)
- BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics)
- BS EN 13141-1:2004 (Air leakage)
- (L70) at a 40,000 hour lifetime

## Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/50HZ
Power Factor	0.9	IP Rating	IP65
Lifetime L70 (hrs)	40000hrs	Overall Diameter (mm)	88
Weight (Kg)	0.371	Height (mm)	105
Product Type	Downlights, Fire-Rated Downlight	Cutout Diameter (mm)	65-72
Operating Temp. (Max) °C	25°C		

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.