

Product Description: 9W IP65 Dimmable Fire Rated Downlight

SKU Code	Colour	Lumens	Beam Angle	Finish Colour
AU-FRLD933MW/30	3000	470	32	Matt White
AU-FRLD933MW/40	4000	565	32	Matt White
AU-FRLD933PC/30	3000	470	32	
AU-FRLD933PC/40	4000	565	32	
AU-FRLD933SN/30	3000	470	32	Satin Nickel
AU-FRLD933SN/40	4000	565	32	Satin Nickel
AU-FRLD933W/30	3000	470	32	White
AU-FRLD933W/40	4000	565	32	White

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Registered Community Design - 001926940
- IP65 high power or COB LED fire rated downlight
- Integrated LED driver connected to loop-in / loop-out FASTFIX connector (Included)
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- Dimmable with leading/trailing edge dimmers
- 7 Year Warranty - *see www.aurora.eu.com for details

Product Specs:

Input Voltage	220~240V AC	Lifetime L70 (hrs)	75000hrs
Overall Diameter (mm)	88	Weight (Kg)	0.453
Height (mm)	105		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.