

Product Description: 40W IP44 622 x 622mm Dimmable Panel

SKU Code	Wattage	Colour	Lumens	Lumens/Watt
AU-LP301A/30	40	3000	3180	80
AU-LP301A/30EM	40	3000	3180	80
AU-LP301A/40	40	4000	3400	85
AU-LP301A/40EM	40	4000	3400	85

Line Drawing

Polar Curve

Colour

Feature & Benefits

- A range of edge-lit LED flat panels for office and commercial lighting
- Suitable for installation in 15 & 24mm T-bar ceilings
- Panel frame RAL9016 White
- May also be surface mounted or suspended
- All versions use optical polycarbonate for even light distribution
- Dimmable (1-10V) and CX options also available
- Up to 20 CX panels can be interconnected and controlled with a AU-DLED801C controller
- IP44 from below when recessed mounted - suitable for use in commercial kitchens, clean rooms, healthcare and similar environments
- High colour rendering index (Ra) 80
- UGR (unified glare rating) - 19 - perfect for use in offices
- DALI options available, please call sales office for details
- Life to 70% lumen maintenance (L70) - 40,000 hours
- 5 Year Warranty - see www.auroralighting.com for details

Product Specs:

Input Voltage	100~240V	IP Rating	IP44
Lifetime L70 (hrs)	40000hrs	Width (mm)	622
Length (mm)	622	Height (mm)	12

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.