




Product Description:

mPro™ Fixed IP65 Dimmable Fire Rated Downlight


Integrated, fire rated 7W LED downlight with driver-on-board. Convertible design to fit ceiling voids as shallow as 47mm. Available in 2700K, 3000K and 4000K. Interchangeable bezels available in white, matt white, polished chrome and satin nickel. Multiple lens options: 40° and 60°. Rated to 30,60 and 90 minute fire ceilings. Complies with BS EN 1365-2: 2014 (fire resistance), BS EN ISO 10140-2: 2010 & BS EN ISO 10140-3: 2010 + A1: 2015 (acoustics), BS EN 13141-1:2004 (Air leakage).

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-MPR03/27	7	2700	560	80	60	White
AU-MPR03/30	7	3000	600	86	60	
AU-MPR03/40	7	4000	640	92	60	

Line Drawing



Polar Curve



Colour

Feature & Benefits

- IP65 with IP65 bezel to order separately
- Patented LEDchroic™ lens provides halogen appearance with LED efficiency, anti-glare and precise beam control
- 60° lens supplied, interchangeable 40° lens - sold separately
- IC cap included for installation
- Separate driver to install below other insulation material
- ErP compliant - High colour rendering index (Ra) >80
- Rated to 30, 60 & 90 minute fire ceilings
- EnEV compliant
- (L70) at a 40,000 hour lifetime
- 5 Year Warranty – see auroralighting.com for details

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.85	IP Rating	IP65
Lifetime L70 (hrs)	40000hrs	Lifetime L80 (Hours)	61000hrs
Lamp Base	None	Overall Diameter (mm)	88
Weight (Kg)	0.307	Projection (mm)	4
Height (mm)	100	Product Type	Downlights
Cutout Diameter (mm)	68-72	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	25°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.