



**Product Description:** mPro™ Adjustable IP65 Dimmable Fire Rated Downlight


Adjustable, integrated, fire rated 7W LED downlight with driver-on-board. Convertible design to fit ceiling voids as shallow as 47mm. Available in 3000K and 4000K. Interchangeable bezels available in white, matt white, polished chrome and satin nickel. Rated to 30,60 and 90 minute fire ceilings. Complies with BS EN 1365-2: 2014 (fire resistance), BS EN ISO 10140-2: 2010 & BS EN ISO 10140-3: 2010 + A1: 2015

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-MPRO4AKMW/27	7	2700	600	86	60	Matt White
AU-MPRO4AKMW/30	7	3000	630	90	60	Matt White
AU-MPRO4AKMW/40	7	4000	660	95	60	Matt White
AU-MPRO4AKPC/27	7	2700	600	86	60	Polished Chrome
AU-MPRO4AKPC/30	7	3000	630	90	60	Polished Chrome
AU-MPRO4AKPC/40	7	4000	660	95	60	Polished Chrome
AU-MPRO4AKSN/27	7	2700	600	86	60	Satin Nickel
AU-MPRO4AKSN/30	7	3000	630	90	60	Satin Nickel
AU-MPRO4AKSN/40	7	4000	660	95	60	Satin Nickel
AU-MPRO4AKW/27	7	2700	600	86	60	White
AU-MPRO4AKW/30	7	3000	630	90	60	White
AU-MPRO4AKW/40	7	4000	660	95	60	White

## Line Drawing

## Polar Curve

## Colour



## Feature &amp; Benefits

## Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.85	IP Rating	IP65
Lifetime L70 (hrs)	40000hrs	Length (mm)	103
Overall Diameter (mm)	98	Projection (mm)	3.5
Height (mm)	103	Product Type	Downlights
Cutout Diameter (mm)	85-85	Operating Temp. (Min) °C	-25°C
Operating Temp. (Max) °C	45°C		

## Compliance &amp; Approvals:



## Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.