

Product Description:

CDM-T 250W Pendant

SKU Code

AU-PHLCD70

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Mains voltage HID high bay pendant light
- Allows compliance with the Building Regulations Approved document L2A/B requiring the use of energy efficient luminaires in commercial buildings
- Comes complete with ballast and floating glass trim
- Requires reflector (AU-PHR12) available in acrylic
- Non-dimmable
- Please note: Ceramic & quartz metal-halide lamps have a warm-up/re-strike time
 5minutes. Therefore these should be used in conjunction with other luminaires that will provide sufficient lighting until the metal-halides reach their full brightness

Product Specs:

Input Voltage	220~240V AC	Overall Diameter (mm)	346
Weight (Kg)	6.797	Height (mm)	490
Base Diameter (mm)	175		

Compliance & Approvals:









Warranty

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.