



Product Description:

75-1000VA Remote Dimmer

SKU Code					
AU-RMD1000RF					
Line Drawing	Polar Curve	Colour			

Feature & Benefits

1000W Dimmer suitable for the Leading edge phase control Hold down switch for dimming Smooth dimming operation from control of dimmable electronic control 0-100% light output • Dimmer module may be transformers, toroidal Complies with the latest Electrical Safety standard for mounted in the ceiling void, Minimum load 75W, maximum transformers, and tungsten lamps WITHOUT de-rating cupboard etc. load 1000W dimmer switches EN 60669-2-Dimmer is controlled by momentary switches, therefore Integrated over-temperature Replaceable HRC fuse to allow 1:2000 & EN 61058protection fuse replacement if damaged by the failure of GZ/GU10 lamps 1:1992+A1 there is no buzzing at the switch position EMC compliance - EN 55015, EN 61000, EN 61547 Not suitable for use with fluorescent lamps Not suitable for LED loads

Product Specs:

	<u> </u>		
Input Voltage	240~240V AC	Width (mm)	45
Length (mm)	145	Weight (Kg)	0.281
Height (mm)	33		

Compliance & Approvals:

Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.