

Product Description: IP65 1 x Signage Module

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle
AU-SN100W	1.2	4500	85	71	120
AU-SN100WW	1.2	3000	100	84	120

Line Drawing

Polar Curve

Colour

Feature & Benefits

- High Power IP65 Signage LED for 8-20cm glowing character, advertisement board, light box or local lighting.
- 1.2W Low power consumption and high lumen value, a long life-span, maintenance-free
- 12V DC low voltage input
- 1pcs SMD5050 single colour
- 120° Beam Angle
- Working temperature -20 to +60°C
- Series-parallel connection circuit, 20pcs for 1 string
- Supplied in packs of 20 modules
- Dimmable up to 15m/75 modules with AU-LEDD9012 dimmable LED driver & AU-DSPLED 1-10V dimmer
- (L70) at a 25,000 hour lifetime
- 3 years warranty - see www.auroralighting.com for details

Product Specs:

Input Voltage	12~12V DC	IP Rating	IP65
Lifetime L70 (hrs)	25000hrs	Width (mm)	35
Length (mm)	45	Weight (Kg)	0.298
Height (mm)	8	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	40°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.