

Product Description: IP65 Wall Light

SKU Code	Wattage
AU-STL883BLU	1.2
AU-STL883GRN	1.2
AU-STL883W	1.2

Line Drawing

Polar Curve

Colour

Feature & Benefits

- IP65 Mains voltage LED light suitable for stair, corridor and low level lighting
- Integrated LED driver - no separate controller required
- Satin silver cast aluminium faceplate
- NON-REPLACEABLE LEDs with up to 30,000 hours life makes fittings ideal for inaccessible locations
- Cool operating temperature
- White, Blue, Green and Red LED versions available (Due to the nature of LED's a slight colour variation from lamp to lamp is possible)
- Suitable for mounting in both dry lined & solid walls. (Separate mounting sleeve supplied for solid wall mounting)
- Non-dimmable
- N.B. Cut-out dimension refers to product when used without the plastic mounting sleeve (With sleeve cutout is 140mm x 140mm)

Product Specs:

Input Voltage	220~240V AC	IP Rating	IP65
Width (mm)	135	Weight (Kg)	0.522
Height (mm)	135		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.