




Product Description:

Versitile  $^{\text{TM}}$  45W 1200 x 300mm Suspended Semi-Transparant Dimmable Panel

Range of suspended edge-lit LED light panels with 60% down and 40% upward light distribution. Lightweight slim aluminium frame in RAL9016 White finish and transparent when switched off, allowing for natural light to pass through without creating shadows great for daylight harvesting. Ideal for office and other commercial applications. Driver mounting box with driver included. Available with alternative suspension methods and in Dali.

| AU-SU101CAK/30 45 3000 4500 100 120 Wh<br>AU-SU101CAK/30D 45 3000 4500 100 120 Wh<br>AU-SU101CAK/40 45 4000 4500 100 120 Wh | SKU Code        |
|---|-----------------|
|   | AU-SU101CAK/30  |
| ALI CUI O CAVAO 4E 4000 4E00 100 100 W  | AU-SU101CAK/30D |
| AU-SU101CAK/40 45 4000 4500 100 120 Wh  | AU-SU101CAK/40  |
| AU-SU101CAK/40D 45 4000 4500 100 120 Wh   | AU-SU101CAK/40D |





## Feature & Benefits

- Suspended LED flat panel for office and commercial lighting
- 60% down and 40% upward light distribution
- Acrylic diffuser is completely transparent when switched off
- Allows natural light to pass through without creating shadows
- 1-10V dimmable
- (L70) at a 50,000 hour lifetime
- 5 Year Warranty see www.auroralighting.com for details

## **Product Specs:**

| Input Voltage            | 100~240V AC |
|--------------------------|-------------|
| Power Factor             | 0.95        |
| Lifetime L70 (hrs)       | 50000hrs    |
| Width (mm)               | 295         |
| Height (mm)              | 15          |
| Operating Temp. (Min) °C | -20°C       |

| Input Frequency          | 50/60HZ |
|--------------------------|---------|
| IP Rating                | IP20    |
| IK Rating                | IK08    |
| Length (mm)              | 1195    |
| Product Type             | Panels  |
| Operating Temp. (Max) °C | 60°C    |

## Compliance & Approvals:

## Warranty

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.