



Product Description: 220-240V 34W 600mmx600mm LED Troffer


UGR19 High efficiency precise optical control Stargrid Troffer with high LED performance 132Lm/w L70 50,000 hrs. T-Bar Grid ceiling or surface mounted, ideal for commercial, hospitality, education applications.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type |
|--------------------|---------|--------|--------|-------------|------------|---------------|---------------|
| AU-TFL60601AK/40 | 34 | 4000 | 4500 | 133 | 70 | RAL9016 | Non Dimmable |
| AU-TFL60601DAAK/40 | 34 | 4000 | 4500 | 133 | 70 | RAL9016 | DALI Dimmable |

Line Drawing

Polar Curve

Colour



Feature & Benefits

Product Specs:

| | | | |
|--------------------------|-------------|--------------------------|---------|
| Input Voltage | 220~240V AC | Input Frequency | 50/60HZ |
| Power Factor | 0.9 | IP Rating | IP40 |
| Lifetime L70 (hrs) | 50000hrs | Width (mm) | 595 |
| Length (mm) | 595 | Height (mm) | 35 |
| Operating Temp. (Min) °C | 0°C | Operating Temp. (Max) °C | 25°C |

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.