




Product Description: 220-240V 15W 600mmx300mm Recessed LED Louvre Troffer


Range of LED luminaires with a double parabolic aluminium louvre system for a Unified Glare Rating (UGR) of <19 which is ideal for office and educational facilities. Available in 600x300mm, 1200x300mm and 1500x300mm to suit different ceiling structures. With a lumen output of up to 3325lm, required illuminance for office and other commercial buildings is confidently achieved. Option for Airflow addition is available; please contact sales office. With SDCM<3, colour consistency across large installations is assured. Supplied with non-dimmable driver as standard. Available in 4000K and a 50,000 hours lifetime to L70.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-TFL60AK/40	15	4000	1500	100	100	RAL9016
AU-TFL60DAK/40	15	4000	1425	95	100	RAL9016

Line Drawing



Polar Curve



Colour

Feature & Benefits

- Great colour consistency with SDCM of < 3
- Single aluminum louver, double parabolic
- Supplied with 1.5 meters flex & plug
- UGR < 19 ideal for use in offices
- IP20 for use indoors
- 5 Year Warranty

Product Specs:

Input Voltage	220~240V	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP20
Lifetime L70 (hrs)	50000hrs	Width (mm)	295
Length (mm)	595	Height (mm)	55
Product Type	Panels	Operating Temp. (Max) °C	25°C

Compliance & Approvals:

Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.