

Product Description: Universal™ IP65 Fixed Fire Rated Downlight

The only Fire Rated Downlight that we know of that is suitable for ANY Bulb technology (halogen, CFL, or LED), along with allowing insulation material to be placed on top of the fitting guard. It also comes fitted with a GU10 lampholder and includes an MR16 Lampholder for convenient choice of bulb type. A truly great product which solves all your specification and installation needs in 1 fell swoop. Lamps not included.

SKU Code	Finish Colour
AU-UNIF783MW	Matt White
AU-UNIF783PC	Polished Chrome
AU-UNIF783SN	Satin Nickel
AU-UNIF783W	White

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Registered Community Design - 001926429 European Patent - EP1726873B1 UK Patent - 2426321B
- Universal fire rated downlight allows the use of halogen, CFL and LED lamps
- Increased ventilation slots allow heat from all lamp types to be effectively dissipated
- Fitted insulation cover cap allows the downlights to be IC rated - covered with insulation material if necessary. Downlight insulation guard not required
- Tested in 30, 60 & 90 minute fire rated ceilings, 2 Year guarantee
- Supplied with GU10 lampholder fitted and optional MR16 lampholder for freedom of lamp choice
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation

Product Specs:

Input Voltage	12~240V AC	IP Rating	IP65
Lamp Base	GU10	Width (mm)	125
Overall Diameter (mm)	89	Weight (Kg)	0.338
Cutout Length (mm)	315	Cutout Width (mm)	155
Height (mm)	152	Cutout Diameter (mm)	72-

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.