





Product Description:

LinearTube™ 1500mm 60W IP69K Tubular Anti-Corrosive


The IP69K LED anti-corrosive batten, LinearTube[™] is designed to work in environments where robust lighting is required, for example the food industry or agricultural sites. The batten can withstand heavy wash down, and has a -20° to 45° ambient operating temperature. The batten can be surface mounted or suspended (suspension kit not supplied), delivering 120lm/W. The internal aluminium heatsink offers enhanced heat dissipation, and the fully polycarbonate diffuser is IK10 rated for impact resistance.


SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-ANTB1500F/40	60	4000	7200	120	120	Frosted White	Non Dimmable

Line Drawing

Polar Curve

Colour





Feature & Benefits

- Fully polycarbonate diffuser with 316 stainless steel end caps
- Internal aluminium heatsink for enhanced heat dissipation
- Delivering 120lm/W
- IP69K rated and designed to work in environments that require a heavy wash down, for example the food industry
- IK10 rated impact resistance
- -20° to 45° ambient operating temperature
- 3 Year Warranty

Product Specs:

Input Voltage	200~240V AC
IP Rating	IP69K
IK Rating	IK10
Overall Diameter (mm)	70
Product Type	Linears
Operating Temp. (Max) °C	45°C

Power Factor	0.9
Lifetime L70 (hrs)	50000hrs
Length (mm)	1500
Weight (Kg)	2.136
Operating Temp. (Min) °C	-20°C

Compliance & Approvals:











vvarranty

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.