


Product Description: UniPac™ 1200mm 36W IP65 Polycarbonate LED Anti-Corrosive


The UniPac™ range of anti-corrosives is the perfect cost effective solution to replace traditional T8 fluorescent fittings. Formed from a single polycarbonate body and using high lumen LED chips, it's engineered for installation in the most challenging environments making the decision to switch to LED that much easier. Also available with microwave sensor and corridor function.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-ANTE236/40	36	4000	3200	89	120	White	Non Dimmable
EN-ANTE236/40EM	36	4000	3200	89	120	White	Emergency
EN-ANTE236/40EMMS	36	4000	3200	89	120	White	
EN-ANTE236/40EMR	36	4000	3200		120	White	Emergency
EN-ANTE236/40MS	36	4000	3200	89	120	White	Microwave
EN-ANTE236/40MSC	36	4000	3200	89	120	White	Microwave with Corridor
EN-ANTEACC							

Line Drawing



Polar Curve



Colour

Feature & Benefits

- IP65 vandal resistant polycarbonate housing and opal diffuser provide smooth, even light distribution with no hot spots
- Ideal for both interior and exterior applications e.g. car parks
- Push fit terminals in both ends for through cable wiring and quick and easy installation
- 20mm conduit entry knockouts on each end cap
- Supplied with mounting clips and cable glands
- Microwave sensor detection range up to 12 metres
- Light detection at 30 lux unless disabled
- Adjustable hold time 5 seconds to 10 minutes
- IK08 impact rating
- 1.5kV surge protection
- 3 year warranty

Product Specs:

Input Voltage	100~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	25000hrs
Lamp Base	Other
Length (mm)	1226
Height (mm)	95
Operating Temp. (Min) °C	-20°C

Input Frequency	50/60HZ
IP Rating	IP65
IK Rating	IK08
Width (mm)	110
Weight (Kg)	1.762
Product Type	Linears
Operating Temp. (Max) °C	40°C

Compliance & Approvals:

Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.