




Product Description: EnPac™ 600mm 20W Polycarbonate LED Batten


Solid and functional, the EnPac™ range of LED battens are an ideal solution for indoor commercial and industrial applications. Designed specifically for LED, their tough IK08 exterior and high transmittance, low glare diffuser provides great performance and light distribution for all internal applications. The EnPac™ range is suitable for ceiling and wall mounting. Large terminal block and through cable conduit entry for easy installation.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-BN620/40	20	4000	2200	110	120	White	Non Dimmable
EN-BN620C/40	20	4000	2200	110	120	White	Non Dimmable

Line Drawing



Polar Curve



Colour

Feature & Benefits

- Sleek aesthetic design - steel housing with polycarbonate diffuser
- Instant start, high output, energy efficient LED light bars are an ideal retrofit solution for T8 fluorescent tubes
- High quality diffuser covering the LED light bars eliminates unwanted glare providing visual comfort
- Surface mounted fitting suitable for most indoor and industrial applications such as warehousing, retail, internal industrial, storage rooms, back office spaces and corridors
- Large terminal block for easy installation. Side conduit, rear entry and through cable wiring
- IK08 impact rating
- 1.5kV surge protection
- 3 year warranty

Product Specs:

Input Voltage	100~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP20
Lifetime L70 (hrs)	40000hrs	IK Rating	IK08
Width (mm)	60	Length (mm)	625
Weight (Kg)	0.879	Height (mm)	58
Product Type	Linears	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	45°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.