

Product Description:

Pola™ 10W IP54 Dimmable Downlight with Remote Driver

The Pola[™] range of dimmable LED downlights are now available in fixed, baffle and adjustable baffle. Supplied with remote driver and 1.2m flex and plug, the range delivers up to 790 lumens. This makes them an ideal cost effective solution for new or existing residential installations, or other applications where traditional compact fluorescent downlights need upgrading to more efficient LED technology.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type |
|-----------------|---------|--------|--------|-------------|------------|---------------|----------|
| EN-DDL16AKSN/30 | 10 | 3000 | 720 | 72 | 90 | Satin Nickel | Dimmable |
| EN-DDL16AKSN/40 | 10 | 4000 | 770 | 77 | 90 | Satin Nickel | Dimmable |
| EN-DDL16AKSN/57 | 10 | 5700 | 780 | 78 | 90 | Satin Nickel | Dimmable |
| EN-DDL16AKW/30 | 10 | 3000 | 720 | 72 | 90 | White | Dimmable |
| EN-DDL16AKW/40 | 10 | 4000 | 770 | 77 | 90 | White | Dimmable |
| EN-DDL16AKW/57 | 10 | 5700 | 780 | 78 | 90 | White | Dimmable |

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Energy efficient dimmable LED downlight for maximum energy
- IP54 rated versions ideal for bathroom installation
- IC-F rated abutted & covered
- EN-DDL14AK IC rated
- Wide range of colour temperatures making it suitable for diverse applications
- Available in fixed, baffled and adjustable baffle versions
- Pre-wired with 1.2m flex and 2-pin plug
- 1.5kV surge protection
- 3 year warranty

Product Specs:

| Input Voltage | 200~240V AC | Input Frequency | 50/60HZ | |
|--------------------|-------------|-----------------------|---------|--|
| Power Factor | 0.9 | IP Rating | IP54 | |
| Lifetime L70 (hrs) | 40000hrs | Overall Diameter (mm) | 115 | |
| Product Type | Downlights | Cutout Diameter (mm) | 90- | |

Compliance & Approvals:











This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.