Product Description: E6060™ 600 x 600mm 30W Non-Dimmable LED Flat Panel

The ultra-slim E6060™ and E1260™ edge-lit LED panel range is suitable for a wide range of applications including office, education and commercial spaces. The advanced aluminium heat sink dissipates unwanted heat allowing for a flat form factor. The range is engineered to deliver a Unified Glare Rating of 19 (UGR19) for even light distribution.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-FP6060A/40	30	4000	2700	90	115	RAL9016	Non Dimmable
EN-FP6060A/40D	30	4000	2500		115	RAL9016	
EN-FP6060A/40EM	30	4000	2500	84	115	RAL9016	
EN-FP6060A/50	30	5000	2700	90	115	RAL9016	Non Dimmable
EN-FP6060A/50D	30	5000	2500		115	RAL9016	
EN-FP6060A/50EM	30	5000	2500	84	115	RAL9016	

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Edge-lit design and optical pattern light guide engineered for even light distribution
- Suitable for installation in 15 & 24mm T-bar ceilings
- SDCM <4 providing consistent light colour quality
- UGR 19 (Unified Glare Rating) - suitable for use in offices
- Flicker free driver - Power Factor >0.9
- Life not affected by frequent switching e.g. when used with occupancy controls
- 1-10V dimmable and separate emergency pack available
- Surface mount box and adjustable suspension kit available
- 1.5kV surge protection
- 3 year warranty

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	40000hrs
Length (mm)	595
Product Type	Panels
Operating Temp. (Max) °C	40°C

Input Frequency	50/60HZ
IP Rating	IP20
Width (mm)	595
Height (mm)	9.5
Operating Temp. (Min) °C	-20°C

Compliance & Approvals:

Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.