







Product Description:


InterLED™ 1200mm 30W Linear

Supplied with 2m suspension cable and surface mount brackets, the InterLEDTM is an LED linear batten suitable for a range of applications. Delivering 100lm/W the opal polycarbonate diffuser ensures uniform light distribution. Available in a choice of white or black finish, with the option to add an emergency pack.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-LN1230BLK/40	30	4000	3000	100	110	Black	Non Dimmable
EN-LN1230EMBLK/40	30	4000	3000	100	110	Black	Emergency
EN-LN1230EMW/40	30	4000	3000	100	110	White	Emergency
EN-LN1230W/40	30	4000	3000	100	110	White	Non Dimmable







Feature & Benefits

- Opal polycarbonate diffuser with uniform distribution
- Delivering 100lm/W
- Supplied with 2m suspension cable & surface mount brackets
- Suitable to be surface mounted 5 Year Warranty or suspended

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.90
Lifetime L70 (hrs)	50000hrs
Width (mm)	50
Weight (Kg)	1.653
Product Type	Linears
Operating Temp. (Max) °C	40°C

Input Frequency	50/60HZ		
IP Rating	IP20		
IK Rating	IK08		
Length (mm)	1200		
Height (mm)	81.5		
Operating Temp. (Min) °C	-20°C		

Compliance & Approvals:













This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.