



SKU Code	Colour	Wattage
A2-DCFE218	4000	36

Line Drawing

Polar Curve

Color

## Product Features:

- Compact fluorescent downlight with polished aluminium reflector
- Suitable for display lighting in shops, offices, showrooms, hotels, etc.
- Accessories include twist and lock bezels, IP44 splash proof lens and floating glass
- Non-dimmable
- Supplied with non-dimmable high frequency electronic ballast as standard
- Lamps included

## Product Specs:

Input Voltage	220~240V AC	Dimmable	No
Technology	CFL	Overall Diameter (mm)	230
Lamp Base	G24q-2 (4-pin)	Weight (Kg)	1.311
Recess Depth (mm)	140	Positional Adjustment	Fixed
Positional Adjustment	Fixed		

## Compliance & Approvals:



## Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.