



Product Description: PL-C (2-Pin) 2 x 26W Fixed CFL Downlight

This is a high quality commercial CFL PL-C 2 x 26W Downlight. Commonly used in corridor or high level lighting locations. They are 4000k and produce a spectacular amount of useful light into the working area.

SKU Code	Wattage	Colour
A2-DCFE226	52	4000

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Compact fluorescent downlight with polished aluminium reflector
- Supplied with non-dimmable high frequency electronic ballast as standard
- For use with long life horizontally mounted compact fluorescent lamps for high efficiency and reduced running costs
- Suitable for display lighting in shops, offices, showrooms, hotels, etc.
- Single & twin lamp versions from 18W to 26W
- Lamps included
- Accessories include twist and lock bezels, IP44 splash proof lens and floating glass
- Non-dimmable
- *Add suffix EM to catalogue number for Emergency option

Product Specs:

Input Voltage	220~240V AC	Lamp Base	G24q-2 (4-pin)
Overall Diameter (mm)	230	Weight (Kg)	1.34
Cutout Diameter (mm)	200-		

Compliance & Approvals:



Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.