

Product Description:

Integrated intumescent material completely seals the downlight and cut-out in the event of a fire. The A2-DLL681 features reduced recess depth for shallow ceiling voids and is intended for use with aluminium reflector lamps only. Registered Community Design 390612-0001/2/3 and UK Patent GB2426321.

Product Image:



MR16 Fire Rated Downlight

Product Features:

- Requires a suitable 12V Constant Voltage Transformer (Not Included)
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- UK Patent GB2426321

Product Specs:

Lamp Type	MR16	Lamp Base	GU5.3
Input Voltage	12~12V AC	Lifetime L70 (hrs)	3000
Dimmable	Yes	Overall Diameter (mm)	85
Recess Depth (mm)	105	Weight (Kg)	0.223

SKU Table and Ordering:

SKU Code	Lumens/Watt	Beam Angle	Finish Colour
A2-DLL681PC	0	36	Polished Chrome
A2-DLL681SN	0	36	Satin Nickel
A2-DLL681W	0	36	White

Compliance & Approvals:



Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.