



Product Description: GU10 Adjustable Fire Rated Downlight

SKU Code	Wattage	Beam Angle
A2-DLM672PC	50	36
A2-DLM672SN	50	36
A2-DLM672W	50	36

Line Drawing

Polar Curve

Colour

### Feature & Benefits

- Registered Community Design 390612-0001/2/3
- UK Patent GB2426321
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Reduced recess depth for shallow ceiling voids
- Not for use with dichroic halogen (cool beam) lamps
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- Lamp not included
- 2 Year guarantee

## Product Specs:

Input Voltage	220~240V AC	Lifetime L70 (hrs)	5000hrs
Lamp Base	GU10	Overall Diameter (mm)	95
Weight (Kg)	0.308	Cutout Diameter (mm)	80-

## Compliance & Approvals:



## Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.