AURORA®
LIGHTING




Product Description: GU10 Adjustable Fire Rated Downlight

Adjustable GU10 Spring Clip Fire Rated Downlight with an integrated intumescent material that completely seals the downlight and cut-out in the event of a fire. Downlight has been tested in 30, 60 and 90 minute fire rated ceilings. Suitable for Halogen, CFL and LED GU10 lamps.

SKU Code	Finish Colour
A2-DLM942PB	Polished Brass
A2-DLM942PC	Polished Chrome
A2-DLM942SN	Satin Nickel
A2-DLM942SS	Satin Silver
A2-DLM942W	White

Line Drawing



Polar Curve

Colour

Feature & Benefits

- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Not for use with dichroic halogen (cool beam) lamps
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- Supplied with GU10 lamp holder fitted
- Reduced height fire rated can allows installation in shallow ceiling voids
- Lamp not included

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
IP Rating	IP20	Lamp Base	GU10
Overall Diameter (mm)	90	Weight (Kg)	0.316
Product Type	Downlights	Cutout Diameter (mm)	75-

Compliance & Approvals:

Warranty:

This product has a warranty period of 2 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.