




Product Description: 23W 6" Dimmable Fixture


The Titan Pro - range of Commercial LED Lighting Fixtures are ideal for retrofitting LED technology into existing outdated installations and can also be used in new construction with our housing frame accessory. Supplied with a quick connect case, Titan Pro light fixtures are easily connected to a recessed fixture frame, fitted with an external 0-10V dimmable driver as standard. The deep baffle allows exceptional control of the light and reduces the glare rating significantly. Featuring CRI>90, this range delivers quality of light to a plethora of commercial spaces. 0-10V Dimming.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AR-DC0623/30	23	3000	1400	61	40	White
AR-DC0623/40	23	4000	1500	66	40	White
AR-DC0623/50	23	5000	1700	74	40	White

Line Drawing



Polar Curve



Colour

Feature & Benefits

- Recessed COB LED Retrofit light fixture for commercial applications
- Excellent CRI>90 for exceptional quality of light
- Deep baffle provides excellent glare control
- Ideal retrofit solution for existing installations or new construction
- Supplied with quick connect case as standard to easily connect to recessed fixture frame junction box
- Supplied with 3 spare friction clips to support retrofit applications
- Beam angles of 40° 6" and 50° 8"
- Operating temperature -4°F to 113°F
- 0-10V dimmable as standard, allows for installation with daylight or occupancy sensors
- Available color temperatures 3000K, 4000K, 5000K
- Non-IC Rated
- (L70) at 50,000 hrs lifetime
- 5 year warranty

Product Specs:

Input Voltage	100~277V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	Damp Location
Lifetime L70 (hrs)	50000hrs	Width (mm)	198
Overall Diameter (mm)	198	Product Type	Downlights
Cutout Diameter (mm)	148-152	Operating Temp. (Min) °C	-10°C
Operating Temp. (Max) °C	45°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.