




Product Description: Esofit Plus 13W 5-6" Retrofit Gimbal Trim


Designed to service the needs of the residential/commercial market, the Aurora Esofit Plus retrofit 4" & 5-6" trims are ideal for replacing existing incandescent, fluorescent and halogen lights with their superior high powered low wattage LED's with CRI>90 for true color rendering. Available in fixed versions with a recessed baffle or adjustable with gimbal feature allowing 355° rotation. The Esofit Plus installs easily into most standard 4" or 5-6" recessed CANs, including IC and NON-IC housings, for both retrofit and new construction. These trims use only 9, 13 or 18 Watts of power & produce 600, 800 and 1200 lumens. Compatible with most line voltage dimmers.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AR-GDL8056/27	13	2700	800	62	90	White
AR-GDL8056/30	13	3000	800	62	90	White
AR-GDL8056/40	13	4000	800	62	90	White
AR-GDL8056/50	13	5000	800	62	90	White

Line Drawing



Polar Curve



Colour

Feature & Benefits

- Fits a range of 4" or 5" - 6" CANS
- Light aluminum body with superior heat dissipation
- Easy installation - E26 socket & quick connector
- 120V inline voltage dimmable
- Power factor >0.9
- IC rated (when used with an IC rated CAN)
- 30 degree tiltable
- 355 degree rotatable
- Compression Clips provided within the pack
- High Color Rendering of Ra > 90
- Polycarbonate diffuser
- Energy Star accredited
- Title 24 High Energy compliance for California
- Suitable for damp locations
- (L70) at 50,000 hour lifetime
- 5 year warranty

Product Specs:

Input Voltage	120~120V AC	Input Frequency	60/60HZ
Power Factor	0.9	IP Rating	Damp Location
Lifetime L70 (hrs)	50000hrs	Lamp Base	E26
Width (mm)	188	Overall Diameter (mm)	188
Product Type	Downlights	Cutout Diameter (mm)	126-146
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	40°C

Compliance & Approvals:



Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.