




**Product Description:** Ostia 230W IP65 Dimmable Highbay


Aurora's Ostia Highbay allows for significant energy saving to be achieved without sacrificing light output or performance levels. Delivering in excess of 100lm/w Ostia outperforms old HID technology, substantially in a compact low profile housing.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AR-HB2301A/40	230	4000	23400	102	120	Satin Silver
AR-HB2301A/50	230	5000	24500	107	120	Satin Silver
AR-HB2301A/60	230	6000	26000	114	120	Satin Silver

**Line Drawing**



**Polar Curve**



**Colour**

## Feature & Benefits

- Suitable for use in warehousing, manufacturing, conference centers, industrial applications, canopies and high end retail applications
- Significant energy savings and maintenance free
- High thermal efficient aluminium heatsink - low operating temperature
- 1-10V dimming function built in as standard - allows for installation with daylight or occupancy sensors
- High power factor 0.95
- Instant on/off, no re-strike delay
- Operating temperature -20°C to 60°C
- Suitable for Wet location, IP65
- 120° beam as standard without reflector, optional 90° or 60° aluminum reflectors and 60° acrylic reflector available
- Suspension, 3/4" all thread conduit entry and wall mounting options
- Supplied with 4.92ft of power cable
- (L70) at 60,000 hour lifetime
- 5 year warranty

## Product Specs:

Input Voltage	100~277V AC	Input Frequency	50/60HZ
Power Factor	0.95	IP Rating	Wet Location
Lifetime L70 (hrs)	60000hrs	IK Rating	IK10
Width (mm)	338	Overall Diameter (mm)	338
Height (mm)	172	Product Type	Highbays
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	60°C

## Compliance & Approvals:



## Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.