


Product Description: Versitile™ 40W 1' x 4' Dimmable Panel

A range of high energy-efficiency edge-lit Versitile™ LED flat panels for office and commercial lighting applications. Suitable for installation in T-bar suspended ceilings. Optional drywall, surface mount or suspension kit accessories are available. Easy installation & maintenance free. Optical polycarbonate diffuser, for even light distribution with 120° beam angle. Ultra-thin white profile frame – depth just 0.39". Total depth including the driver box 1.96". CRI>80. High power factor - 0.90. Aurora's dimmable panels provide a simple 0-10V solution that is compatible with stand alone 0-10V dimmers as well as larger lighting control systems and allows for installation with daylight or occupancy sensors. Suitable for damp locations, IP44. DLC (DesignLights Consortium®) certified. (L70) at 50,000 hour lifetime. 5 Year warranty

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AR-LP114C4DD347/30	40	3000	4000	100	120	RAL9016
AR-LP114C4DD347/30EM	40	3000	4000	100	120	RAL9016
AR-LP114C4DD347/35	40	3500	4000	100	120	RAL9016
AR-LP114C4DD347/35EM	40	3500	4000	100	120	RAL9016
AR-LP114C4DD347/40	40	4000	4100	103	120	RAL9016
AR-LP114C4DD347/40EM	40	4000	4100	103	120	RAL9016
AR-LP114C4DD347/50	40	5000	4200	105	120	RAL9016
AR-LP114C4DD347/50EM	40	5000	4200	105	120	RAL9016



Feature & Benefits

- A range of high energy-efficiency edge-lit LED flat panels for office and commercial lighting applications
- Suitable for installation in T-bar suspended ceilings. Optional drywall, surface mount or suspension kit accessories are available
- Easy installation & maintenance free
- Optical polycarbonate diffuser, for even light distribution with 120° beam angle
- Ultra-thin white profile frame – depth just 0.39"
- Total depth including the driver box 1.96"
- CRI>80
- High power factor - 0.90
- Aurora's dimmable panels provide a simple 0-10V solution that is compatible with stand alone 0-10V dimmers as well as larger lighting control systems and allows for installation with daylight or occupancy sensors
- Suitable for damp locations, IP44
- DLC (DesignLights Consortium®) certified
- (L70) at 50,000 hour lifetime
- 5 Year warranty

Product Specs:

Input Voltage	100~347V AC
Power Factor	0.99
Lifetime L70 (hrs)	50000hrs
Length (mm)	1212
Product Type	Panels
Operating Temp. (Max) °C	40°C

Input Frequency	60/60HZ
IP Rating	Damp Location
Width (mm)	301
Height (mm)	10
Operating Temp. (Min) °C	-20°C

Compliance & Approvals:



Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.