



Product Description: 12W Round Top Bollard

Our bollard luminaires are designed with a domed top that allows them to blend easily into many applications. Constructed for wet locations, their durable design can withstand the harsh conditions of any outdoor environment, including coastal locations. With a powder coated, corrosion proof aluminum exterior and clear polycarbonate lens, our bollards are available in either a black, satin silver or bronze finish.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour |
|----------------------|---------|--------|--------|-------------|------------|---------------|
| AR-PST110/LEDBLK/BLU | | | 100 | | | Black |
| AR-PST110/LEDBLK/W | 12 | 4000 | 345 | 29 | 110 | Black |
| AR-PST110/LEDBR/BLU | | | 100 | | | Bronze |
| AR-PST110/LEDBR/W | 12 | 4000 | 345 | 29 | 110 | Bronze |
| AR-PST110/LEDSS/BLU | | | 100 | | | Satin Silver |
| AR-PST110/LEDSS/W | 12 | 4000 | 345 | 29 | 110 | Satin Silver |

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Die cast aluminum bollard LED light
- Powder coated corrosion resistant finish
- Clear polycarbonate lens
- Supplied with LED driver
- Suitable for wet locations / IP54
- AU-JM02 anchor fixings for concrete available (not included)
- AU-RM01 root mount kit for earth available (not included)
- Non-dimmable
- 5 Year warranty
- Suitable for damp locations

Product Specs:

| | | | |
|--------------------------|----------|--------------------------|---------------|
| Input Voltage | 100~277V | Input Frequency | 50/60HZ |
| Power Factor | 0.95 | IP Rating | IP54 |
| Lifetime L70 (hrs) | 50000hrs | Overall Diameter (mm) | 165 |
| Weight (Kg) | 5.693 | Height (mm) | 1000 |
| Base Diameter (mm) | 230 | Product Type | Ground Lights |
| Operating Temp. (Min) °C | -10°C | Operating Temp. (Max) °C | 40°C |

Compliance & Approvals:



Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.