




Product Description: VersiLite™ 30W 2' x 2' Dimmable 0-10V Troffer

The VersiLite Troffer features high efficiency, quality and performance achieving up to 125lm/w. These luminaires are designed with the latest LED technology to produce highly efficient lighting, which provides pleasant and uniform light distribution. The VersiLite have a clean, modern look and an even distribution which makes them an ideal solution for either drop ceilings in offices, schools, hospitality and other commercial applications.


The Aurora Troffer offers lower power consumption, longer life, 0-10V dimming and zero maintenance (no re-lamping required) than the standard fluorescent fixture and

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
AR-TF2230BD/35	30	3500	3750	125	120	Matt White	Dimmable
AR-TF2230BD/40	30	4000	3750	125	120	Matt White	Dimmable
AR-TF2230BD/50	30	5000	3750	125	120	Matt White	Dimmable

Line Drawing



Polar Curve



Colour

Feature & Benefits

- A range of high energy-efficiency LED Troffers for office and commercial lighting applications
- Suitable for installation in T-bar suspended ceilings.
- Optical polycarbonate diffuser, for even light distribution with 120° beam angle
- Total depth including the driver box 3.93"
- CRI>80
- High power factor - 0.90
- Aurora's dimmable panels provide a simple 0-10V solution that is compatible with stand alone 0-10V dimmers as well as larger lighting control systems and allows for installation with daylight or occupancy sensors
- Operating temperature -4°F to 104°F
- Available color temperatures 3500K, 4000K, 5000K
- Suitable for damp locations
- DLC Premium (DesignLights Consortium®) certified
- (L70) at 50,000 hour lifetime
- 5 Year warranty

Product Specs:

Input Voltage	100~277V AC	Input Frequency	60/60HZ
Power Factor	0.9	IP Rating	Damp Location
Lifetime L70 (hrs)	50000hrs	Width (mm)	603
Length (mm)	603	Weight (Kg)	3.9
Height (mm)	100	Product Type	Troffer
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	40°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.