

Product Description: Moon 35W without Barn Doors

Derived from the traditional theater style lantern, the Moon Slim range updates the spotlight with modern compact light source and a variety of reflector beam angle choices.

The intensity of the CDM-Tm lamp is ideal for retail where contrast within a lighting scheme ensures that customers are drawn into and through the store, bringing attention to the brand messaging.

SKU Code	Wattage	Colour	Beam Angle	Finish Colour
AR-TM01135MMB/3	35	3000	30	Matt Black
AR-TM01135MMB/4	35	4200	30	Matt Black
AR-TM01135MS/3	35	3000	30	Silver
AR-TM01135MS/4	35	4200	30	Silver
AR-TM01135MW/3	35	3000	30	White
AR-TM01135MW/4	35	4200	30	White
AR-TM01135NMB/3	35	3000	20	Matt Black
AR-TM01135NMB/4	35	4200	20	Matt Black
AR-TM01135NS/3	35	3000	20	Silver
AR-TM01135NS/4	35	4200	20	Silver
AR-TM01135NW/3	35	3000	20	White
AR-TM01135NW/4	35	4200	20	White
AR-TM01135SMB/3	35	3000	80	Matt Black
AR-TM01135SMB/4	35	4200	80	Matt Black
AR-TM01135SS/3	35	3000	80	Silver
AR-TM01135SS/4	35	4200	80	Silver
AR-TM01135SW/3	35	3000	80	White
AR-TM01135SW/4	35	4200	80	White
AR-TM01135WMB/3	35	3000	45	Matt Black
AR-TM01135WMB/4	35	4200	45	Matt Black
AR-TM01135WS/3	35	3000	45	Silver
AR-TM01135WS/4	35	4200	45	Silver
AR-TM01135WW/3	35	3000	45	White
AR-TM01135WW/4	35	4200	45	White

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Suitable for dry locations only
- For use with track - flexibility of track is particularly suited to retail or display use, where store layouts change with the seasons or as new merchandise is introduced
- Choice of 4 beam angles - direct all the light to the right place
- Narrow and medium beam reflectors are optimized for retail featuring the 'Retail Hot Spot' for effective accent lighting
- Rotation of 310° and a swing of 180°, to allow precise focusing
- Barn Door accessory available for extra beam control
- High CRI of 87, and excellent quantity of light provides 'retail sparkle'
- Choice of 3 color finishes, including textured matt black
- Available with 3000K CDM-Tm lamp
- Supplied with track adaptor suitable for use with Nordic GES single circuit track

Product Specs:

Input Voltage	120~120V AC	IP Rating	IP20
Lifetime L70 (hrs)	15000hrs	Width (mm)	140
Length (mm)	215	Weight (Kg)	1.64
Projection (mm)	229		

Compliance & Approvals:

Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.