



Product Description: TC-DD 14W Emergency Lamp

SKU Code	Colour	Lumens	Lumens/Watt	Wattage	CRI
AU-2D14EM/45	4500	1200	86	14	80

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Direct replacement for 28W TC-DD compact fluorescent lamps in bulkhead fittings etc.
- 3 hour maintained emergency backup
- Remove the fluorescent starter switch and replace the fluorescent lamp. For maximum energy saving bypass the ballast (electronic ballasts must be bypassed)
- Compliant with Building Regulations Approved document L2A / B requiring the use of energy efficient luminaires in buildings other than dwellings
- Suitable for use in offices, warehouses, car parks, stairwells / corridors etc or difficult access / maintenance applications
- Instant start without flickering
- Suitable for use with PIR with no reduction in lamp life.
- Non-dimmable
- Life to 70% lumen maintenance (L70) - 15,000 Hours

Product Specs:

Input Voltage	100~260V AC	Input Frequency	50/60HZ
Lamp Base	GR10Q	Overall Height (mm)	30
Lamp Type	PAR38	Weight (Kg)	0.517
Lifetime Hours	15000hrs		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.