



**Product Description:** Primo<sup>™</sup> Fixed 11W Architectural Downlight


Exceptional architectural downlight range, Primo features an ultra-slim bezel a deep baffle to reduce glare. Compatible with a dedicated LED module, the complete ICE<sup>™</sup> Lamp range, or AOne<sup>™</sup> Smart GU10 lamps, with multiple bezel options, the Primo is perfect for a range of different applications. High-quality components feature SDCM <1 for complete colour consistency and CRI98 for true colour representation.

SKU Code	Colour	Lumens	Lumens/Watt	Wattage	Beam Angle	Finish Colour	SKU Type	Bezel Type
AU-ADST1BIP/27	2700	340	31	11	18	Matt White	Triac Dimmable	IP Rated
AU-ADST1BIPDA/27	2700	340	31	11	18	Matt White	DALI Dimmable	IP Rated
AU-ADST1BIPV/27	2700	340	31	11	18	Matt White	1-10V Dimmable	IP Rated
AU-ADST1BOV/27	2700	160	15	11	18	Matt White	Triac Dimmable	Oval
AU-ADST1BOVDA/27	2700	160	15	11	18	Matt White	DALI Dimmable	Oval
AU-ADST1BOVV/27	2700	160	15	11	18	Matt White	1-10V Dimmable	Oval
AU-ADST1BPN/27	2700	260	24	11	18	Matt White	Triac Dimmable	Pinhole
AU-ADST1BPND/27	2700	260	24	11	18	Matt White	DALI Dimmable	Pinhole
AU-ADST1BPNV/27	2700	260	24	11	18	Matt White	1-10V Dimmable	Pinhole
AU-ADST1BRB/27	2700	400	37	11	18	Matt White	Triac Dimmable	Round Bezel
AU-ADST1BRBDA/27	2700	400	37	11	18	Matt White	DALI Dimmable	Round Bezel
AU-ADST1BRBV/27	2700	400	37	11	18	Matt White	1-10V Dimmable	Round Bezel

## Line Drawing

## Polar Curve

## Colour



Matt White

## Feature &amp; Benefits

- Ultra slim 1.5mm bezel
- Citizen CLU028 LED chip for superior light output and control
- SDCM < 1 for complete colour consistency
- CRI98 for true colour representation
- Trimless plaster-in mount available for seamless installation
- FastRFix rapid install system connector included
- Triac dimmable constant current LED driver included
- Use with AU-ADFRC for 30 and 60 minute fire rating in solid timber joists
- 5 Year Warranty

## Product Specs:

Input Voltage	220~240V DC	Input Frequency	50/60HZ
Power Factor	0.93	IP Rating	IP20
Lifetime L70 (hrs)	50000	Overall Diameter (mm)	90
Cutout Diameter (mm)	75	Product Type	Downlights
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	45°C
Height (mm)	115		

## Compliance &amp; Approvals:



## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.