

Product Description:

Gama de luminarias individuales y dobles de policarbonato LED anticorrosivas con cuerpo y difusor de policarbonato antivandálico. Para facilitar la instalación, el difusor se sujeta permanentemente con dos clips y la bandeja de engranajes está equipada con restricciones. El accesorio se suministra con soportes de montaje para montaje o suspensión en techo y pared. Se suministran clips de acero inoxidable antimanipulación con la luminaria. Múltiples puntos de entrada del conducto de extracción están instalados en la parte posterior y los extremos de la carcasa. Reemplazo de bandejas de engranajes disponibles. 5 años de garantía.

Product Image:



Product Features:

- Vandal proof polycarbonate body and diffuser - ideal for food preparation areas
- Diffuser permanently attached by two clips for ease of installation
- Gear tray restraints for ease of installation and maintenance
- Optional mounting brackets (included) allow for ceiling, wall or suspended mounting
- Anti-tamper stainless steel clips supplied as standard
- Multiple drill-out conduit entry points at the back and ends of housing
- IK08 impact rating
- Replacement gear trays available - contact sales office for details
- (L70) at a 25,000 hour lifetime
- 3 Year Warranty – see www.auroralighting.com for details
- Emergency, Microwave and DALI options available
- Microwave sensor detection range up to 12 meters.
- Adjustable detection range, hold time and lux level settings

Luminaria doble Anti-corrosiva 1500mm IP65


Product Specs:

Technology	LED	Input Voltage	220~240V AC
LED Chip	5630	Number of LEDs	130
Positional Adjustment	Fijo	Input Frequency	50/60HZ
Lifetime L70 (hrs)	25000	Power Factor	0.95
Dimmable	No	Luminaire Distribution	Directo
Positional Adjustment	Fijo	IP Rating	IP65
IK Rating	IK08	Fire Protection	No
SDCM	4	Dali	Yes
Operating Env. Temp. (Max) °C	25°C	Optic Material	PC
Length (mm)	1574	Width (mm)	140
Weight (Kg)	2.880		

Line Drawing



Polar Curve



SKU Table and Ordering:

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-ANT1504A/40	60	4000	5700	95	120	Gris
AU-ANT1504A/40D	60	4000	5700	95	120	Gris
AU-ANT1504A/40DALI	60	4000	5700	95	120	Gris
AU-ANT1504A/40EM	60	4000	5700	95	120	Gris
AU-ANT1504A/40MS	60	4000	5700	95	120	Gris
AU-ANT1504A/40MSEM	60	4000	5700	95	120	Gris
AU-ANT1504A/60	60	6000	5810	97	120	Gris
AU-ANT1504A/60D	60	6000	5810	0	120	Gris
AU-ANT1504A/60DALI	60	6000	5810	97	120	Gris
AU-ANT1504A/60EM	60	6000	5810	97	120	Gris
AU-ANT1504A/60MS	60	6000	5810	97	120	Gris
AU-ANT1504A/60MSEM	60	6000	5810	97	120	Gris

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 aos. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.