

Product Description: 1500mm IP65 Triple Anti-Corrosive

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
AU-ANT1570A/40	65	4000	6100	94	98	Grey	Non Dimmable
AU-ANT1570A/40DALI	65	4000	6100		98	Grey	DALI Dimmable
AU-ANT1570A/40EM	65	4000	6100	94	98	Grey	Emergency

Line Drawing

Polar Curve

Colour

Feature & Benefits

- IP65 vandal resistant polycarbonate LED anti-corrosive fitting - ideal for kitchens, car parks, boiler rooms, factories & farm buildings
- Replicates T8 light distribution (excellent vertical and horizontal illumination)
- Anti-tamper 316 stainless steel clips supplied as standard
- Engineered LED light engine maximises light distribution and uniformity
- Reduced glare diffuser
- 20mm conduit knockout entry points
- IK08 impact rating
- Replacement gear trays available - contact sales office for details
- (L70) at a 40,000 hour lifetime
- Emergency versions available
- 5 Year Warranty – see www.auroralighting.com for details

Product Specs:

Input Voltage	240~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP65
Lifetime L70 (hrs)	40000hrs	IK Rating	IK08
Width (mm)	160	Length (mm)	1570
Weight (Kg)	3.49	Height (mm)	110
Product Type	Linears	Operating Temp. (Max) °C	25°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.