Product Description: 15W IP65 Bulkhead

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-BH104BO	15	4000	850	57	120	Black
AU-BH104BP	15	4000	1100	74	120	Black
AU-BH104WO	15	4000	850		120	White
AU-BH104WP	15	4000	1100		120	White

Line Drawing

Polar Curve

Colour

Feature & Benefits

- IP65 Polycarbonate LED bulkhead
- 3 Hour maintained emergency back-up option (AU-BH104EM) and microwave sensor option (AU-BH104MS) available
- Life not affected by frequent switching e.g. when used with occupancy controls
- Tough polycarbonate body for vandal resistance
- Opal diffuser
- Wall or ceiling mounting
- 20mm conduit entries
- Emergency version has integral 3 hour battery back-up
- Non-dimmable
- (L70) - 25,000 hours
- 3 Years Warranty - *see www.auroralighting.com for details

Product Specs:

Input Voltage	240~240V AC	Input Frequency	50/60HZ
IP Rating	IP65	Lifetime L70 (hrs)	25000hrs
Overall Diameter (mm)	280	Weight (Kg)	0.788
Projection (mm)	83		

Compliance & Approvals:

Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.