




Product Description: CX7[™] Fixed 7W Fire Rated Downlight

Introducing the latest fire rated IP65 downlight to the Aurora portfolio, the CX7[™] is a colour switchable downlight. Supplied complete with a polycarbonate white IP65 bezel (satin nickel and polished chrome IP65 bezels available separately) and integrated driver with loop in/loop out terminal block. The CX7[™] is a colour switchable fire rated downlight, switchable between 3000K, 4000K and 5700K

SKU Code	Wattage	Colour	Lumens	Beam Angle	Finish Colour	SKU Type
AU-CX7	7	3000K	580	60	White	Dimmable
AU-CX7	7	4000K	620	60	White	Dimmable
AU-CX7	7	5700K	620	60	White	Dimmable

Line Drawing



Polar Curve

Colour



White

Feature & Benefits

- Colour temperature can be switched between 3000K, 4000K and 5700K
- Lumen output ranges from 580lm at 3000K, 620lm at 4000K and 620lm at 5700K
- Colour temperature must be selected prior to installation
- Integrated driver on board with loop in/out terminal block for quick and easy installation
- Supplied with a White IP65 bezel (Polished Chrome & Satin Nickel bezel finishes sold separately)
- Insulation coverable
- Patented fire rated downlight without intumescent
- Tested in 30, 60 & 90 min solid timber joist fire rated ceilings
- Tested in 30 min i-joist and open web joist fire rated ceilings
- Edge-to-edge multifaceted polycarbonate lens for low glare and halogen like appearance
- Wide 60° beam angle delivers increased light distribution
- 3 Year Warranty

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/50HZ
Power Factor	0.9	IP Rating	IP65
Lifetime L70 (hrs)	35000hrs	Overall Diameter (mm)	88
Weight (Kg)	0.236	Height (mm)	80
Product Type	Downlights, Fire-Rated Downlight	Cutout Diameter (mm)	65-70
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	25°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.