Product Description: 9.5W IP44 Low Profile Downlight

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Finish Colour	SKU Type
AU-DL1008BW/30	9.5	3000	350	37	White	Non Dimmable
AU-DL1008BW/40	9.5	4000	400	43	White	Non Dimmable

Line Drawing

Polar Curve

Colour

Feature & Benefits

- IP44 Rated
- 34mm low profile edge-lit LED downlight suitable for use in limited recess space
- SMD LEDs
- Supplied with 30cm cable
- Requires remote 24V DC LED driver (not included)
- 1-10V Dimmable with AU-LEDD9024
- Available in White finish
- (L70) at a 25,000 hour lifetime
- 3 Year Warranty - see www.auroralighting.com for details

Product Specs:

Input Voltage	~24V DC
Power Factor	0.9
Lifetime L70 (hrs)	25000hrs
Overall Diameter (mm)	120
Height (mm)	34
Operating Temp. (Max) °C	25°C

Input Frequency	50/60HZ
IP Rating	IP44
Width (mm)	120
Weight (Kg)	0.168
Cutout Diameter (mm)	105-

Compliance & Approvals:

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.